



**DS S 2F - Foam Station**

|                                  |                         |
|----------------------------------|-------------------------|
| Article #                        | 700100                  |
| Maximum inlet pressure, water    | 30 bar / 450 psi        |
| Maximum temperature, inlet water | 70°C                    |
| Max. temperature for foaming     | 50°C                    |
| Air pressure required            | 3-6 bar                 |
| Water inlet                      | 1/2"                    |
| Air inlet                        | 1/4"                    |
| Max. length of discharge hose    | 35 meter                |
| Type of discharge hose           | Process Cleaners A/S    |
| Quick couplings                  | Standard                |
| Flush nozzle                     | Standard                |
| Foam nozzle                      | Standard                |
| Product concentration            | 1-8%, dep. on viscosity |
| Foam spraying water usage        | 8-12 litre per minute   |
| Water for flushing               | 30 litre per minute     |
| Size: width X height X depth     | 200 x 300 x120          |

**DS S 3F - Foam Station Plus**



|                                  |                         |
|----------------------------------|-------------------------|
| Article #                        | 700200                  |
| Maximum inlet pressure, water    | 30 bar / 450 psi        |
| Maximum temperature, inlet water | 70°C                    |
| Max. temperature for foaming     | 50°C                    |
| Air pressure required            | 3-6 bar                 |
| Water inlet                      | 1/2"                    |
| Air inlet                        | 1/4"                    |
| Max. length of discharge hose    | 35 meter                |
| Type of discharge hose           | Process Cleaners A/S    |
| Quick couplings                  | 1/2"                    |
| Flush nozzle                     | Standard                |
| Disinfections nozzle             | Standard                |
| Foam nozzle                      | Standard                |
| Product concentration            | 1-8%, dep. on viscosity |
| Foam spraying water usage        | 8-12 litre per minute   |
| Water for flushing               | 30 litre per minute     |
| Size: width X height X depth     | 500 x 300 x130          |